



BOLLARDS






Features

IP65.
Eco-friendly LED technology along with energy efficiency and free maintenance.
Precise optical technology and anti-dazzle design create a visual comfort efficiently and high performance.


Application

For illuminating or identifying pathway, garden and park etc.




Luminaire: die-cast aluminium, powder-coated.
Bracket: aluminium, powder-coated.
Ground spike: steel, powder-coated.
Input: AC 100-240V
LED: OSRAM 1.2Wx6(350mA)
LED color: CW NW WW
Color: BF

GA-206A-GP-1-75




NW: 125°d
WW: 110°d




Luminaire: die-cast aluminium, powder-coated.
Bracket: aluminium, powder-coated.
Ground spike: steel, powder-coated.
Input: AC 100-240V
LED: OSRAM 1.2Wx6(350mA)
LED color: CW NW WW
Color: BF

GA-206Q-GP-1-75




NW: 125°d
WW: 110°d




Luminaire: die-cast aluminium, powder-coated.
Bracket: aluminium, powder-coated.
Ground spike: steel, powder-coated.
Input: AC 100V/110V/120V/220V/230V/240V
LED: SSC Acriche 1Wx16
LED color: CW WW
Color: BF

GA-216A




WW: 125°d

Bollards



Luminaire: die-cast aluminium, powder-coated.
 Bracket: aluminium, powder-coated.
 Ground spike: steel, powder-coated.
 Input: AC 100V/110V/120V/220V/230V/240V
 LED: SSC Acriche 1Wx16
 LED color: CW WW
 Color: BF



GA-216Q

Spike for ground mounted.



AC-210A
 spike: aluminium,
 powder-coated.



GA-206A
 GA-206Q




AC-215A
 spike: aluminium,
 powder-coated.




GA-206A
 GA-206Q




AC-220A
 spike: aluminium,
 powder-coated.



GA-206A
 GA-206Q



GA-216A
 GA-216Q






Features


- IP65.
- Eco-friendly LED technology along with the energy savings and free of maintenance.
- Patent thermal management guarantees a long lifespan.
- Anti-dazzle design create a visual comfort.
- No UV or IR radiation in the light beam.
- Either mounting box or earth spike for portable applications.

Application


Single-sided light output suitable for pathways, driveways or squares.




GA-203A-GP-1-75



Luminaire: die-cast aluminium, powder-coated.
 Bracket: aluminium, powder-coated.
 Ground spike: die-cast aluminium, powder-coated.
 Cable: H05RN-F 3x1.0mm'
 Input: AC 100-240V
 LED: OSRAM 1.2Wx3(350mA)
 LED color: CW NW WW
 Color: BF



GA-203Q-GP-1-75



Luminaire: die-cast aluminium, powder-coated.
 Bracket: aluminium, powder-coated.
 Ground spike: die-cast aluminium, powder-coated.
 Cable: H05RN-F 3x1.0mm'
 Input: AC 100-240V
 LED: OSRAM 1.2Wx3(350mA)
 LED color: CW NW WW
 Color: BF

Spike for ground mounted.

